

PAC GS3 Range

Readers—HF

909022118 – PAC OneProx™ GS3 HF Vandal Resistant Reader - blue

The Vandal Resistant Reader is designed to work in the most demanding of operating environments as it provides a robust, intruder-graded access reader. The Vandal Resistant Reader is ideal for internal or external installations.



- Raised key symbol on the front with audible and visual user feedback for Equality Act compliance
- Comes with pre-connected 2m cable for ease of installation
- Supports the following ID Devices:
 - PAC
 - KeyPAC
 - Wiegand (many variants)
- Integral Tamper circuit and Mounting Plate
- Reader line tamper configurable when used in conjunction with PAC 512 controllers

Part Number(s)	909022118 – PAC OneProx™ GS3 HF Vandal Resistant Reader - blue
Supported ID Device Formats	PAC Ops™ Lite, PAC Ops™
Supported Output Protocols	PAC32, PAC64, Wiegand
Audio / Visual Indicators	Audible Sounder and Red/Green LEDs
RFid Frequency	High Frequency (13.56MHz)
Maximum Read Range	40 mm / 1.57 in.
Tamper Output	Certified to EN 50131-1 and EN 50131-3
Recommended Cabling	PAC output 6-core 24 AWG alarm cable (unscreened) Wiegand output 5-core 22 AWG cable
Power input(s)	12–24V DC, <100mA @ 12V DC
Dimensions	100 (w) x 100 (h) x 16 (d) mm / 3.94 (w) x 3.94 (h) x 0.63 (d) in.
Weight	0.442 kg / 0.974 lb
Material	UL rated Polycarbonate
Operating Temperature	-40°C to +66°C / -40°F to 151°F
Operating Humidity	10% to 85% Relative Humidity
Warranty	Lifetime against electronic failure
Standards Compliance	UKCA, CE, FCC, IC, RoHS & WEEE compliant
Environment	IP67 – Indoor / Outdoor weather resistant
Intruder Grading	Security Grade 3